



...advanced chemical
solutions for industry...

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

A114 SUPER POWER

Revision 10

Revision date 2015-06-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	A114 SUPER POWER
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	Assured Solutions Ltd
Address	Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS
Web	www.chemicalsuppliers.uk.com
Telephone	+44 (0)1530 272922
Fax	+44 (0)1530 272921
Email	sales@assuredsolutionsltd.co.uk
Email address of the competent person	sales@assuredsolutionsltd.co.uk

1.4. Emergency telephone number


Emergency telephone number	01530 272 922
Company	ASSURED SOLUTIONS LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/38 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes and skin.
2.1.2. Classification - EC 1272/2008	Skin Corr. 1A: H314;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Precautionary Statement: Prevention	P102 - Keep out of reach of children. P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

A114 SUPER POWER

Revision 10
Revision date 2015-06-16

2.2. Label elements

Precautionary Statement: Response	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ or /if you feel unwell. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P363 - Wash contaminated clothing before reuse.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

2.3. Other hazards

Other hazards	SPILLAGE MAY CREATE SLIP HAZARD.
----------------------	----------------------------------

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0		1 - 10%	Xn; R20/21/22 Xi; R36/38	
SODIUM METASILICATE PENTA HYDRATE		6834-92-0	229-912-9	01-2119449811-37 01-2119449811-37	1 - 10%	C; R34	
TETRA POTASSIUM PYROPHOSPHATE		7320-34-5	230-785-7	01-2119489369-18	1 - 10%	Xi; R36	
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5	01-2119457892-27	0 - 0.5%	C; R35	
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)		57-55-6	200-338-0		0 - 0.5%		

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					80 - 90%		
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		0.5 - 1%	Carc. 2: H351; Acute Tox. 4: H302; Eye Irrit. 2: H319;	
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0		1 - 10%	Acute Tox. 4: H302; Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332;	
SODIUM METASILICATE PENTA HYDRATE		6834-92-0	229-912-9	01-2119449811-37 01-2119449811-37	1 - 10%	Met. Corr. 1: H290; Skin Corr. 1B: H314; Eye Dam. 1: H318; STOT SE 3: H335;	
TETRA POTASSIUM PYROPHOSPHATE		7320-34-5	230-785-7	01-2119489369-18	1 - 10%	Eye Irrit. 2: H319;	
ALCOHOL ETHOXYLATE		68439-46-3			0.5 - 1%	Acute Tox. 4: H302; Eye Dam. 1: H318;	
POTASSIUM SALT OF ARYL ETHER PHOSPHATE ESTER		72283-31-9			0.5 - 1%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5	01-2119457892-27	0 - 0.5%	Skin Corr. 1A: H314;	
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)		57-55-6	200-338-0		0 - 0.5%		
PERFUME					0 - 0.5%		
DYE					0 - 0.5%		

SECTION 4: First aid measures

4.1. Description of first aid measures

A114 SUPER POWER

Revision 10

Revision date 2015-06-16

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

A114 SUPER POWER

Revision 10

Revision date 2015-06-16

8.1.1. Exposure Limit Values

2 BUTOXY ETHANOL (2-Butoxyethanol)	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
PROPYLENE GLYCOL (Propane-1,2-diol particulates)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)	WEL 8-hr limit ppm: 150	WEL 8-hr limit mg/m3: 474
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Sodium hydroxide	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	In case of splashing, wear:.. Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Green
Odour	Characteristic
pH	< 12.5
Initial boiling point	100
Relative density	1.045 NOMINAL

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No data is available on this product.
Skin corrosion/irritation	May cause degreasing of the skin. May cause severe irritation to eyes and skin.

SECTION 12: Ecological information

A114 SUPER POWER

Revision 10

Revision date 2015-06-16

12.1. Toxicity

	No data is available on this product.
--	---------------------------------------

12.2. Persistence and degradability

	DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE. Inorganic materials are inherently not biodegradable however those present in this formulation/product are either of no known significant environmental hazard or are readily neutralised to form inert salts.
--	---

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

15.2. Chemical safety assessment

	No chemical Safety assessment has been carried out by the supplier.
--	---

SECTION 16: Other information

Other information

Revision

	This document differs from the previous version in the following areas: 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response.
--	---

Text of risk phrases in Section 3

	R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed. R34 - Causes burns. R35 - Causes severe burns. R36/38 - Irritating to eyes and skin. R36 - Irritating to eyes.
--	--

Text of Hazard Statements in Section 3

	Acute Tox. 4: H302 - Harmful if swallowed. Eye Irrit. 2: H319 - Causes serious eye irritation. Carc. 2: H351 - Suspected of causing cancer . Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled Skin Irrit. 2: H315 - Causes skin irritation. Met. Corr. 1: H290 - May be corrosive to metals. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Eye Dam. 1: H318 - Causes serious eye damage. STOT SE 3: H335 - May cause respiratory irritation. Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
--	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--