



...advanced chemical
solutions for industry...

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

D402 DE SILT

Revision 3

Revision date 2015-06-03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	D402 DE SILT
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	Assured Solutions Ltd
Address	Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS
Web	www.chemicalsuppliers.uk.com
Telephone	+44 (0)1530 272922
Fax	+44 (0)1530 272921
Email	sales@assuredsolutionsltd.co.uk
Email address of the competent person	sales@assuredsolutionsltd.co.uk

1.4. Emergency telephone number

Emergency telephone number	01530 272 922
Company	ASSURED SOLUTIONS LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Main hazards	No Significant Hazard
--------------	-----------------------

2.2. Label elements

Precautionary Statement: Prevention	P102 - Keep out of reach of children.
Precautionary Statement: Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES
Risk phrases	No Significant Hazard

2.3. Other hazards

Other hazards	SPILLAGE MAY CREATE SLIP HAZARD.
---------------	----------------------------------

SECTION 3: Composition/information on ingredients

3.2. Mixtures

D402 DE SILT

Revision 3

Revision date 2015-06-03

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					60 - 70%		
Formaldehyde...% (Formaldehyde)	605-001-00-5	50-00-0	200-001-8		0 - 0.5%	Carc. Cat. 3; R40 T; R23/24/25 C; R34 R43	
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0		1 - 10%	Xn; R20/21/22 Xi; R36/38	
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	F; R11 Xi; R36 R67	
ANIONIC ACRYLAMIDE COPOLYMER					0.5 - 1%		
DYE					0 - 0.5%		

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					60 - 70%		
Formaldehyde...% (Formaldehyde)	605-001-00-5	50-00-0	200-001-8		0 - 0.5%	Carc. 1B: H350; Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; Skin Corr. 1B: H314; Skin Sens. 1: H317;	
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0		1 - 10%	Acute Tox. 4: H302; Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332;	
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
ANIONIC ACRYLAMIDE COPOLYMER					0.5 - 1%		
DYE					0 - 0.5%		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. No irritation expected. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe. (this does not apply for controlled, professional use).
--	---

D402 DE SILT

Revision 3

Revision date 2015-06-03

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

2 BUTOXY ETHANOL (2-Butoxyethanol)	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Formaldehyde...% (Formaldehyde)	WEL 8-hr limit ppm: 2	WEL 8-hr limit mg/m3: 2.5
	WEL 15 min limit ppm: 2	WEL 15 min limit mg/m3: 2.5
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Not normally required.
8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	In case of splashing, wear:.. Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Not normally required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

D402 DE SILT

Revision 3

Revision date 2015-06-03

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Blue
Odour	Mild
pH	7.0 NOMINAL
Initial boiling point	100
Relative density	1.00 NOMINAL

Water solubility

	Soluble in water.
--	-------------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No data is available on this product.
----------------	---------------------------------------

SECTION 12: Ecological information

12.1. Toxicity

ANIONIC ACRYLAMIDE COPOLYMER	Daphnia EC50/48h: 212mg/l mg/l
---------------------------------	--------------------------------

	No data is available on this product.
--	---------------------------------------

12.2. Persistence and degradability

	More than 90% biodegradable.
--	------------------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

15.2. Chemical safety assessment

	No chemical Safety assessment has been carried out by the supplier.
--	---

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 1 - REACH. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Disposal. 12 - 12.1. Toxicity. 15 - 15.2. Chemical safety assessment.
Text of risk phrases in Section 3	R11 - Highly flammable. R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed. R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed.

D402 DE SILT

Revision 3

Revision date 2015-06-03

Other information

Text of Hazard Statements in Section 3	R34 - Causes burns. R36/38 - Irritating to eyes and skin. R36 - Irritating to eyes. R40 - Limited evidence of a carcinogenic effect. R43 - May cause sensitisation by skin contact. R67 - Vapours may cause drowsiness and dizziness. Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. STOT SE 3: H336 - May cause drowsiness or dizziness.
---	---

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--