



...advanced chemical
solutions for industry...

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

EP 00140

Revision 3

Revision date 2015-08-04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	EP 00140
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	Assured Solutions Ltd
Address	Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS
Web	www.chemicalsuppliers.uk.com
Telephone	+44 (0)1530 272922
Fax	+44 (0)1530 272921
Email	sales@assuredsolutionsltd.co.uk
Email address of the competent person	sales@assuredsolutionsltd.co.uk

1.4. Emergency telephone number


Emergency telephone number	01530 272 922
Company	ASSURED SOLUTIONS LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Eye Irrit. 2: H319;
--------------------------------------	---------------------

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Precautionary Statement: Prevention	P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

EP 00140

Revision 3

Revision date 2015-08-04

2.3. Other hazards

Other hazards	SPILLAGE MAY CREATE SLIP HAZARD.
---------------	----------------------------------

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					70 - 80%		
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		1 - 10%	Carc. Cat. 3; R40 Xn; R22 Xi; R36	
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	F; R11 Xi; R36 R67	
BLOCK COPOLYMER OF PROPYLENE AND ETHYLENE OXIDES		69227-21-0			1 - 10%		
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5	01-2119457892-27	0 - 0.5%	C; R35	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					70 - 80%		
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		1 - 10%	Carc. 2: H351; Acute Tox. 4: H302; Eye Irrit. 2: H319;	
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
BLOCK COPOLYMER OF PROPYLENE AND ETHYLENE OXIDES		69227-21-0			1 - 10%		
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5	01-2119457892-27	0 - 0.5%	Skin Corr. 1A: H314;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	-------------------------------------------------------------------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---------------------------------------------------------

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	-----------------------------------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area.
--	--------------------------------------------------

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	-------------------------------------------------------------------------

EP 00140

Revision 3

Revision date 2015-08-04

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm:	400	WEL 8-hr limit mg/m3:	999
	WEL 15 min limit ppm:	500	WEL 15 min limit mg/m3:	1250
	WEL 8-hr limit mg/m3 total - inhalable dust:	-	WEL 15 min limit mg/m3 total - inhalable dust:	-
	WEL 8-hr limit mg/m3 total - respirable dust:	-	WEL 15 min limit mg/m3 total - respirable dust:	-
Sodium hydroxide	WEL 8-hr limit ppm:	-	WEL 8-hr limit mg/m3:	-
	WEL 15 min limit ppm:	-	WEL 15 min limit mg/m3:	2
	WEL 8-hr limit mg/m3 total - inhalable dust:	-	WEL 15 min limit mg/m3 total - inhalable dust:	-
	WEL 8-hr limit mg/m3 total - respirable dust:	-	WEL 15 min limit mg/m3 total - respirable dust:	-

DNEL: Derived no-effect level.

No data is available on this product.

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	In case of splashing, wear: Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear
Odour	Mild
pH	8.5 NOMINAL
Initial boiling point	100
Relative density	.98 NOMINAL

Water solubility

Soluble in water.

EP 00140

Revision 3

Revision date 2015-08-04

SECTION 10: Stability and reactivity**10.2. Chemical stability**

Stable under normal conditions.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

No data is available on this product.

SECTION 12: Ecological information**12.1. Toxicity**

No data is available on this product.

12.2. Persistence and degradability

DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE.

SECTION 13: Disposal considerations**General information**

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information**Further information**

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information**15.2. Chemical safety assessment**

No chemical Safety assessment has been carried out by the supplier.

SECTION 16: Other information**Other information****Revision**

This document differs from the previous version in the following areas:.

- 1 - REACH.
- 2 - 2.1.2. Classification - EC 1272/2008.
- 2 - Hazard pictograms.
- 2 - Signal Word.
- 2 - Precautionary Statement: Prevention.
- 2 - Precautionary Statement: Response.
- 2 - Precautionary Statement: Disposal.
- 8 - DNEL: Derived no-effect level.
- 12 - 12.1. Toxicity.
- 15 - 15.2. Chemical safety assessment.

Text of risk phrases in Section 3

- R11 - Highly flammable.
- R22 - Harmful if swallowed.
- R35 - Causes severe burns.
- R36 - Irritating to eyes.
- R40 - Limited evidence of a carcinogenic effect.
- R67 - Vapours may cause drowsiness and dizziness.

Text of Hazard Statements in Section 3

- Acute Tox. 4: H302 - Harmful if swallowed.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Carc. 2: H351 - Suspected of causing cancer .
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
- STOT SE 3: H336 - May cause drowsiness or dizziness.
- Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.

Further information

EP 00140

Revision 3

Revision date 2015-08-04

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------
