



...advanced chemical
solutions for industry...

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

EP 11062 LUMINOL CLEAN

Revision 2

Revision date 2015-06-25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	EP 11062 LUMINOL CLEAN
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	Assured Solutions Ltd
Address	Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS
Web	www.chemicalsuppliers.uk.com
Telephone	+44 (0)1530 272922
Fax	+44 (0)1530 272921
Email	sales@assuredsolutionsltd.co.uk
Email address of the competent person	sales@assuredsolutionsltd.co.uk

1.4. Emergency telephone number


Emergency telephone number	01530 272 922
Company	ASSURED SOLUTIONS LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Eye Irrit. 2: H319; Aquatic Chronic 3: H412;
--------------------------------------	--

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Hazard Statement	Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P264 - Wash thoroughly after handling. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

EP 11062 LUMINOL CLEAN

Revision 2
Revision date 2015-06-25

2.2. Label elements

Precautionary Statement: Disposal	P337+P313 - If eye irritation persists: Get medical advice/attention.
	P501 - Dispose of contents/container to REQUIREMENTS OF LOCAL AUTHORITIES

2.3. Other hazards

Other hazards	SPILLAGE MAY CREATE SLIP HAZARD.
----------------------	----------------------------------

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	F; R11 Xi; R36 R67	
ALCOHOL ETHOXYLATE		68439-46-3			1 - 10%	Xn; R22 Xi; R41	
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0	01-2119475108-36	1 - 10%	Xn; R20/21/22 Xi; R36/38	
Benzyl C12-16 Alkyldimethyl, Chlorides		68424-85-1	270-325-2	01-2119970550-39	0.5 - 1%	C; R34 Xn; R21/22 N; R50	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					80 - 90%		
trisodium nitrilotriacetate	607-620-00-6	5064-31-3	225-768-6		0.5 - 1%	Carc. 2: H351; Acute Tox. 4: H302; Eye Irrit. 2: H319;	
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
ALCOHOL ETHOXYLATE		68439-46-3			1 - 10%	Acute Tox. 4: H302; Eye Dam. 1: H318;	
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0	01-2119475108-36	1 - 10%	Acute Tox. 4: H302; Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332;	
TETRA POTASSIUM PYROPHOSPHATE		7320-34-5	230-785-7	01-2119489369-18	0.5 - 1%	Eye Irrit. 2: H319;	
Benzyl C12-16 Alkyldimethyl, Chlorides		68424-85-1	270-325-2	01-2119970550-39	0.5 - 1%	Acute Tox. 4: H302; Skin Corr. 1B: H314; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;	
PERFUME					0 - 0.5%		
Sodium hydroxide	011-002-00-6	1310-73-2	215-185-5	01-2119457892-27	0 - 0.5%	Skin Corr. 1A: H314;	
DYE					0 - 0.5%		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

EP 11062 LUMINOL CLEAN

Revision 2

Revision date 2015-06-25

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

2 BUTOXY ETHANOL (2-Butoxyethanol)	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

DNEL: Derived no-effect level.

No data is available on this product.

Exposure Pattern - Workers

2 BUTOXY ETHANOL	Acute inhalation - Systemic effects	663 mg/m ³	
	Acute inhalation - Local effects	246 mg/m ³	Acute dermal - Systemic effects 89 mg/kg
	Long-term - dermal - Systemic effects	75 mg/kg	

Exposure Pattern - General population

EP 11062 LUMINOL CLEAN

Revision 2

Revision date 2015-06-25

Exposure Pattern - General population

2 BUTOXY ETHANOL	Acute inhalation - Systemic effects	426 mg/m ³	
	Acute dermal - Systemic effects	44.5 mg/kg	Acute oral - Systemic effects
	Long-term - inhalation - Local effects	123 mg/kg	Long-term - dermal - Systemic effects
	Long-term - oral - Systemic effects	3.2 mg/kg	

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Not normally required.
8.2.2. Individual protection measures	Not normally required.
Eye / face protection	In case of splashing, wear:.. Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Not normally required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Green
Odour	Perfumes
pH	9 - 10.5
Solubility	Soluble in water

9.2. Other information

Specific gravity	1 - 1.03
-------------------------	----------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No data is available on this product.
Skin corrosion/irritation	May cause irritation to eyes.
Carcinogenicity	No carcinogenic effects reported.

11.1.4. Toxicological Information

Benzyl C12-16 Alkyldimethyl, Chlorides	Oral Rat LD50: 200-2000mg/kg
---	-------------------------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data is available on this product.
--	---------------------------------------

12.2. Persistence and degradability

	DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE. Inorganic materials are inherently not biodegradable however those present in this formulation/product are either of no known significant environmental hazard or are readily neutralised to form inert salts.
--	---

12.3. Bioaccumulative potential

EP 11062 LUMINOL CLEAN

Revision 2

Revision date 2015-06-25

12.3. Bioaccumulative potential

No data is available on this product.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.2. Chemical safety assessment

No chemical Safety assessment has been carried out by the supplier.

SECTION 16: Other information

Other information

Revision

This document differs from the previous version in the following areas:.

- 1 - REACH.
- 2 - 2.1.2. Classification - EC 1272/2008.
- 2 - Hazard pictograms.
- 2 - Signal Word.
- 2 - Precautionary Statement: Prevention.
- 2 - Precautionary Statement: Response.
- 2 - Precautionary Statement: Disposal.
- 8 - 8.2.2. Individual protection measures.
- 8 - DNEL: Derived no-effect level.
- 12 - 12.1. Toxicity.
- 15 - 15.2. Chemical safety assessment.

Text of risk phrases in Section 3

- R11 - Highly flammable.
- R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.
- R21/22 - Harmful in contact with skin and if swallowed.
- R22 - Harmful if swallowed.
- R34 - Causes burns.
- R36/38 - Irritating to eyes and skin.
- R36 - Irritating to eyes.
- R41 - Risk of serious damage to eyes.
- R50 - Very toxic to aquatic organisms.
- R67 - Vapours may cause drowsiness and dizziness.

Text of Hazard Statements in Section 3

- Acute Tox. 4: H302 - Harmful if swallowed.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Carc. 2: H351 - Suspected of causing cancer .
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
- STOT SE 3: H336 - May cause drowsiness or dizziness.
- Eye Dam. 1: H318 - Causes serious eye damage.
- Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
- Skin Irrit. 2: H315 - Causes skin irritation.
- Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.