



...advanced chemical
solutions for industry...

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

EP 15143 VISCOUS ALLOY WHEEL CLEANER CONCENTRATE

Revision 0

Revision date 2015-09-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	EP 15143 VISCOUS ALLOY WHEEL CLEANER CONCENTRATE
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	Assured Solutions Ltd
Address	Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS
Web	www.chemicalsuppliers.uk.com
Telephone	+44 (0)1530 272922
Fax	+44 (0)1530 272921
Email	sales@assuredsolutionsltd.co.uk
Email address of the competent person	sales@assuredsolutionsltd.co.uk

1.4. Emergency telephone number


Emergency telephone number	01530 272 922
Company	ASSURED SOLUTIONS LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36/38 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes and skin.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Eye Irrit. 2: H319;

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation.
Precautionary Statement: Prevention	P280 - Wear protective gloves/protective clothing/eye protection/face protection.

EP 15143 VISCOUS ALLOY WHEEL CLEANER CONCENTRATE

Revision 0

Revision date 2015-09-16

2.2. Label elements

Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Phosphoric acid...% (Orthophosphoric acid) WATER	015-011-00-6	7664-38-2	231-633-2	01-2119485924-24	10 - 20% 60 - 70%	C; R34	
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0	01-2119475108-36	1 - 10%	Xn; R20/21/22 Xi; R36/38	
Methanol	603-001-00-X	67-56-1	200-659-6		1 - 10%	F; R11 T; R23/24/25-39/23/24/25	
XANTHAN GUM		11138-66-2	234-394-2		0.5 - 1%		
ALCOHOL ETHOXYLATE		68439-46-3			0.5 - 1%	Xn; R22 Xi; R41	
PERFUME					0 - 0.5%		
Dipentene	601-029-00-7	138-86-3	205-341-0		0 - 0.5%	R10 Xi; R38 R43 N; R50/53	
HEXYL CINNAMAL		101-86-0			0 - 0.5%		
DYE					0 - 0.5%		

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Phosphoric acid...% (Orthophosphoric acid) WATER	015-011-00-6	7664-38-2	231-633-2	01-2119485924-24	10 - 20% 60 - 70%	Skin Corr. 1B; H314;	
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0	01-2119475108-36	1 - 10%	Acute Tox. 4: H302; Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332;	
Methanol	603-001-00-X	67-56-1	200-659-6		1 - 10%	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370;	
XANTHAN GUM		11138-66-2	234-394-2		0.5 - 1%		
ALCOHOL ETHOXYLATE		68439-46-3			0.5 - 1%	Acute Tox. 4: H302; Eye Dam. 1: H318;	
PERFUME					0 - 0.5%		
Dipentene	601-029-00-7	138-86-3	205-341-0		0 - 0.5%	Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;	
HEXYL CINNAMAL		101-86-0			0 - 0.5%		
DYE					0 - 0.5%		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	No Significant Hazard.
-------------------	------------------------

EP 15143 VISCOUS ALLOY WHEEL CLEANER CONCENTRATE

Revision 0

Revision date 2015-09-16

4.1. Description of first aid measures

Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon dioxide (CO2).
--	-----------------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Wear suitable protective equipment. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	---

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

EP 15143 VISCOUS ALLOY WHEEL CLEANER CONCENTRATE

Revision 0

Revision date 2015-09-16

8.1.1. Exposure Limit Values

2 BUTOXY ETHANOL (2-Butoxyethanol)	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 123
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 101.2
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Methanol	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 333
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:
Phosphoric acid...% (Orthophosphoric acid)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 1
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: 2
	WEL 8-hr limit mg/m3 total - inhalable dust: WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - inhalable dust: WEL 15 min limit mg/m3 total - respirable dust:

DNEL: Derived no-effect level.

No data is available on this product.

Exposure Pattern - Workers

2 BUTOXY ETHANOL	Acute inhalation - Systemic effects 663 mg/m ³	
	Acute inhalation - Local effects 246 mg/m ³	Acute dermal - Systemic effects 89 mg/kg
	Long-term - dermal - Systemic effects 75 mg/kg	

Exposure Pattern - General population

2 BUTOXY ETHANOL	Acute inhalation - Systemic effects 426 mg/m ³	
	Acute dermal - Systemic effects 44.5 mg/kg	Acute oral - Systemic effects 13.4 mg/kg
	Long-term - inhalation - Local effects 123 mg/kg	Long-term - dermal - Systemic effects 38 mg/kg
	Long-term - oral - Systemic effects 3.2 mg/kg	

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Not normally required.
8.2.2. Individual protection measures	Wear suitable protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

EP 15143 VISCOUS ALLOY WHEEL CLEANER CONCENTRATE

Revision 0

Revision date 2015-09-16

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Various
Odour	Mild
pH	1 - 3
Relative density	1.05 - 1.1
Solubility	Soluble in water

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation Irritating to eyes and skin.

SECTION 12: Ecological information

12.2. Persistence and degradability

DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE. Inorganic materials are inherently not biodegradable however those present in this formulation/product are either of no known significant environmental hazard or are readily neutralised to form inert salts.

12.3. Bioaccumulative potential

No data is available on this product.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

14.1. UN number

The product is not classified as dangerous for carriage.

14.2. UN proper shipping name

The product is not classified as dangerous for carriage.

14.3. Transport hazard class(es)

The product is not classified as dangerous for carriage.

14.4. Packing group

The product is not classified as dangerous for carriage.

14.5. Environmental hazards

The product is not classified as dangerous for carriage.

14.6. Special precautions for user

The product is not classified as dangerous for carriage.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

EP 15143 VISCOUS ALLOY WHEEL CLEANER CONCENTRATE

Revision 0

Revision date 2015-09-16

15.2. Chemical safety assessment

	No chemical Safety assessment has been carried out by the supplier.
--	---

SECTION 16: Other information

Other information

Text of risk phrases in Section 3	<p>R10 - Flammable R11 - Highly flammable. R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed. R22 - Harmful if swallowed. R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed. R34 - Causes burns. R36/38 - Irritating to eyes and skin. R38 - Irritating to skin. R39/23/24/25 - Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R41 - Risk of serious damage to eyes. R43 - May cause sensitisation by skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p>
Text of Hazard Statements in Section 3	<p>Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT SE 1: H370 - Causes damage to organs . Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Sens. 1: H317 - May cause an allergic skin reaction. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.</p>

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--