



...advanced chemical
solutions for industry...

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

EP 8505

Revision 1

Revision date 2015-08-04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	EP 8505
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	Assured Solutions Ltd
Address	Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS
Web	www.chemicalsuppliers.uk.com
Telephone	+44 (0)1530 272922
Fax	+44 (0)1530 272921
Email	sales@assuredsolutionsltd.co.uk
Email address of the competent person	sales@assuredsolutionsltd.co.uk

1.4. Emergency telephone number


Emergency telephone number	01530 272 922
Company	ASSURED SOLUTIONS LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Eye Irrit. 2: H319;
--------------------------------------	---------------------

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Precautionary Statement: Prevention	P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

EP 8505

Revision 1
Revision date 2015-08-04

2.3. Other hazards

Other hazards	SPILLAGE MAY CREATE SLIP HAZARD.
---------------	----------------------------------

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					80 - 90%		
LAURYL BETAINE		66455-29-6	266-368-1		0 - 0.5%	Xi; R38-41	
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	F; R11 Xi; R36 R67	
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)		57-55-6	200-338-0	01-2119456809-23	1 - 10%		
PERFUME					0.5 - 1%		
ALCOHOL ETHOXYLATE		68439-46-3			0.5 - 1%	Xn; R22 Xi; R41	
AMYL CINNAMAL		122-40-7			0 - 0.5%		
LINALOOL		78-70-6			0 - 0.5%		
CITRONELLOL		106-22-9			0 - 0.5%		
L LIMONENE		5989-27-5			0 - 0.5%	Xi; R38-43 N; R50/53 R10	
CINNAMYL ALCOHOL		104-54-1			0 - 0.5%		
BUTYLPHENYL METHYLPROPIONAL		106-22-9			0 - 0.5%		

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER					80 - 90%		
LAURYL BETAINE		66455-29-6	266-368-1		0 - 0.5%		
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		1 - 10%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)		57-55-6	200-338-0	01-2119456809-23	1 - 10%		
PERFUME					0.5 - 1%		
ALCOHOL ETHOXYLATE		68439-46-3			0.5 - 1%	Acute Tox. 4: H302; Eye Dam. 1: H318;	
AMYL CINNAMAL		122-40-7			0 - 0.5%		
LINALOOL		78-70-6			0 - 0.5%		
CITRONELLOL		106-22-9			0 - 0.5%		
L LIMONENE		5989-27-5			0 - 0.5%		
CINNAMYL ALCOHOL		104-54-1			0 - 0.5%		
BUTYLPHENYL METHYLPROPIONAL		106-22-9			0 - 0.5%		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

EP 8505

Revision 1
Revision date 2015-08-04**4.1. Description of first aid measures**

Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.
-----------	-----------------------------------------------------------------------------------------------------------------------------

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Use extinguishing media appropriate to the surrounding fire conditions.
--	-------------------------------------------------------------------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---------------------------------------------------------

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	-----------------------------------------------------

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area.
--	--------------------------------------------------

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	-------------------------------------------------------------------------

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--------------------------------------------------------------------------------------------------------------------

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

EP 8505

Revision 1
Revision date 2015-08-04

8.1.1. Exposure Limit Values

Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm: 400 WEL 15 min limit ppm: 500 WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 999 WEL 15 min limit mg/m3: 1250 WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
PROPYLENE GLYCOL (Propane-1,2-diol particulates)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
PROPYLENE GLYCOL (Propane-1,2-diol total vapour and particulates)	WEL 8-hr limit ppm: 150 WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 474 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -

DNEL: Derived no-effect level.

	No data is available on this product.
--	---------------------------------------

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	In case of splashing, wear:.. Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear
Odour	Pleasant
Initial boiling point	100
Relative density	.995 NOMINAL

Water solubility

	Soluble in water.
--	-------------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No data is available on this product.
Skin corrosion/irritation	May cause irritation to eyes. Seek medical attention if irritation or symptoms persist.

SECTION 12: Ecological information

EP 8505

Revision 1
Revision date 2015-08-04

12.1. Toxicity

No data is available on this product.

12.2. Persistence and degradability

DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.2. Chemical safety assessment

No chemical Safety assessment has been carried out by the supplier.

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 1 - REACH. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Disposal. 8 - DNEL: Derived no-effect level. 9 - 9.1. Information on basic physical and chemical properties (Appearance). 9 - 9.1. Information on basic physical and chemical properties (Colour). 9 - 9.1. Information on basic physical and chemical properties (Odour). 12 - 12.1. Toxicity. 15 - 15.2. Chemical safety assessment.
Text of risk phrases in Section 3	R10 - Flammable R11 - Highly flammable. R22 - Harmful if swallowed. R36 - Irritating to eyes. R38 - Irritating to skin. R41 - Risk of serious damage to eyes. R43 - May cause sensitisation by skin contact. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 - Vapours may cause drowsiness and dizziness.
Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use,

EP 8505

Revision 1

Revision date 2015-08-04

Further information

	storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------
