



...advanced chemical
solutions for industry...

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

G715

Revision 3

Revision date 2015-06-26

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	G715
REACH	ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES.

1.3. Details of the supplier of the safety data sheet

Company	Assured Solutions Ltd
Address	Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS
Web	www.chemicalsuppliers.uk.com
Telephone	+44 (0)1530 272922
Fax	+44 (0)1530 272921
Email	sales@assuredsolutionsltd.co.uk
Email address of the competent person	sales@assuredsolutionsltd.co.uk

1.4. Emergency telephone number


Emergency telephone number	01530 272 922
Company	ASSURED SOLUTIONS LTD 24hrs

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	F; R11 Xi; R36 R67 Symbols: F: Highly flammable. Xi: Irritant.
Main hazards	Highly flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.

G715

Revision 3

Revision date 2015-06-26

2.2. Label elements

Precautionary Statement: Prevention	<p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 - Keep container tightly closed.</p> <p>P240 - Ground/bond container and receiving equipment.</p> <p>P241 - Use explosion-proof electrical/ventilating/lighting// equipment.</p> <p>P242 - Use only non-sparking tools.</p> <p>P243 - Take precautionary measures against static discharge.</p> <p>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P264 - Wash thoroughly after handling.</p> <p>P271 - Use only outdoors or in a well-ventilated area.</p> <p>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p>
Precautionary Statement: Response	<p>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337+P313 - If eye irritation persists: Get medical advice/attention.</p> <p>P370+P378 - In case of fire: Use suitable media to extinguish.</p>
Precautionary Statement: Storage	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 - Store in a well-ventilated place. Keep cool.</p> <p>P405 - Store locked up.</p>
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		50 - 60%	F; R11 Xi; R36 R67	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		50 - 60%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
WATER					40 - 50%		
ALCOHOL ETHOXYLATE		68439-46-3			0 - 0.5%	Acute Tox. 4: H302; Eye Dam. 1: H318;	
DYE					0 - 0.5%		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

G715

Revision 3

Revision date 2015-06-26

5.1. Extinguishing media

Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Isopropanol (Propan-2-ol)	WEL 8-hr limit ppm:	400	WEL 8-hr limit mg/m ³ :	999
	WEL 15 min limit ppm:	500	WEL 15 min limit mg/m ³ :	1250
	WEL 8-hr limit mg/m ³ total - inhalable dust:	-	WEL 15 min limit mg/m ³ total - inhalable dust:	-
	WEL 8-hr limit mg/m ³ total - respirable dust:	-	WEL 15 min limit mg/m ³ total - respirable dust:	-

DNEL: Derived no-effect level.

No data is available on this product.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear suitable protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection -
Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Not normally required. Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

G715

Revision 3
Revision date 2015-06-26

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Blue
Odour	Alcoholic
Flash point	12
Relative density	.910 NOMINAL

Water solubility

	Soluble in water.
--	-------------------

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	May cause dizziness and headache.
Skin corrosion/irritation	Irritating to eyes and skin. May cause degreasing of the skin.
Repeated or prolonged exposure	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

SECTION 12: Ecological information

12.2. Persistence and degradability

	DETERGENTS IN THIS FORMULATION ARE >90% BIODEGRADABLE. Evaporates readily.
--	--


SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1219
--	--------

14.2. UN proper shipping name

	ISOPROPANOL
--	-------------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-

G715

Revision 3

Revision date 2015-06-26

14.3. Transport hazard class(es)

IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	II
---------------	----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L

SECTION 15: Regulatory information**15.2. Chemical safety assessment**

	No chemical Safety assessment has been carried out by the supplier.
--	---

SECTION 16: Other information**Other information**

Revision	This document differs from the previous version in the following areas: 1 - REACH. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal. 8 - DNEL: Derived no-effect level. 12 - 12.1. Toxicity. 15 - 15.2. Chemical safety assessment.
Text of risk phrases in Section 3	R11 - Highly flammable. R36 - Irritating to eyes. R67 - Vapours may cause drowsiness and dizziness.
Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information
--	--

G715

Revision 3

Revision date 2015-06-26

Further information

	relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	---
