



...advanced chemical solutions for industry...

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/7

K 1012 PENERATING OIL

Revision 0
Revision date 2016-03-23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| | |
|--------------|--|
| Product name | K 1012 PENERATING OIL |
| REACH | ALL INGREDIENTS IN THIS FORMULATION HAVE BEEN REGISTERED (WHERE REQUIRED) FOR APPLICABLE USES. |

1.3. Details of the supplier of the safety data sheet

| | |
|---------------------------------------|--|
| Company | Assured Solutions Ltd |
| Address | Unit H Westminster Industrial Estate Measham Derbyshire DE12 7DS |
| Web | www.chemicalsuppliers.uk.com |
| Telephone | +44 (0)1530 272922 |
| Fax | +44 (0)1530 272921 |
| Email | sales@assuredsolutionsltd.co.uk |
| Email address of the competent person | sales@assuredsolutionsltd.co.uk |

1.4. Emergency telephone number

| | |
|----------------------------|--------------------------------|
| Emergency telephone number | 01530 272 922 |
| Company | ASSURED SOLUTIONS LTD 24hrs |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

| | |
|--------------------------------------|---|
| 2.1.1. Classification - 1999/45/EC | F+; R12 Symbols: F+: Extremely flammable. |
| Main hazards | Extremely flammable. Harmful: may cause lung damage if swallowed. |
| 2.1.2. Classification - EC 1272/2008 | Flam. Liq. 2: H225; Asp. Tox. 1: H304; |

2.2. Label elements

| | |
|-------------------------------------|---|
| Hazard pictograms | |
| Signal Word | Danger |
| Hazard Statement | Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. |
| Precautionary Statement: Prevention | P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |

K 1012 PENERATING OIL

Revision 0

Revision date 2016-03-23

2.2. Label elements

| | |
|--|---|
| Precautionary Statement: Response | P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use suitable media to extinguish. |
| Precautionary Statement: Storage | P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. |
| Precautionary Statement: Disposal | P501 - Dispose of contents/container to requirements of local authorities |

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification | M-factor. |
|--|--------------|------------|-----------|---------------------------|--------------|------------------------|-----------|
| Kerosine - unspecified - distillates (petroleum), hydrotreated light | 649-422-00-2 | 64742-47-8 | 265-149-8 | 01-2119484819-18 | 50 - 60% | Xn; R65 | |
| Propane | 601-003-00-5 | 74-98-6 | 200-827-9 | | 10 - 20% | F+; R12 | |
| Butane | 601-004-00-0 | 106-97-8 | 203-448-7 | | 10 - 20% | F+; R12 | |
| Isobutane | 601-004-00-0 | 75-28-5 | 200-857-2 | | 10 - 20% | F+; R12 | |
| Acetone | 606-001-00-8 | 67-64-1 | 200-662-2 | 01-2119471330-49 | 1 - 10% | F; R11 Xi; R36 R66 R67 | |
| MINERAL OIL | | | | | 1 - 10% | | |
| WOOLGREASE FATTY ACID | | 68440-09-5 | | | 1 - 10% | | |
| EMULSOGEN E | | | | | 1 - 10% | | |

EC 1272/2008

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification | M-factor. |
|--|--------------|------------|-----------|---------------------------|--------------|--|-----------|
| Kerosine - unspecified - distillates (petroleum), hydrotreated light | 649-422-00-2 | 64742-47-8 | 265-149-8 | 01-2119484819-18 | 50 - 60% | Asp. Tox. 1: H304; | |
| Propane | 601-003-00-5 | 74-98-6 | 200-827-9 | | 10 - 20% | Flam. Gas 1: H220; | |
| Butane | 601-004-00-0 | 106-97-8 | 203-448-7 | | 10 - 20% | Flam. Gas 1: H220; | |
| Isobutane | 601-004-00-0 | 75-28-5 | 200-857-2 | | 10 - 20% | Flam. Gas 1: H220; | |
| Acetone | 606-001-00-8 | 67-64-1 | 200-662-2 | 01-2119471330-49 | 1 - 10% | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; | |
| MINERAL OIL | | | | | 1 - 10% | | |
| WOOLGREASE FATTY ACID | | 68440-09-5 | | | 1 - 10% | | |
| EMULSOGEN E | | | | | 1 - 10% | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------|---|
| Inhalation | Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention. |
| Eye contact | May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist. |
| Skin contact | May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. |

K 1012 PENERATING OIL

Revision 0

Revision date 2016-03-23

4.1. Description of first aid measures

| | |
|-----------|---|
| Ingestion | Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label. |
|-----------|---|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--|---|
| | Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam. |
|--|---|

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| | Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back. |
|--|---|

5.3. Advice for firefighters

| | |
|--|---|
| | Wear suitable respiratory equipment when necessary. |
|--|---|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|--|---|
| | Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment. Adopt best Manual Handling considerations when handling, carrying and dispensing. |
|--|---|

6.2. Environmental precautions

| | |
|--|---|
| | Do not allow product to enter drains. Prevent further spillage if safe. |
|--|---|

6.3. Methods and material for containment and cleaning up

| | |
|--|---|
| | Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. |
|--|---|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|--|--|
| | Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing. |
|--|--|

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--|--|
| | Keep in a cool, dry, well ventilated area. Keep containers tightly closed. |
|--|--|

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

K 1012 PENERATING OIL

Revision 0

Revision date 2016-03-23

8.1.1. Exposure Limit Values

| | | |
|-----------|--|---|
| Acetone | WEL 8-hr limit ppm: 500 WEL 15 min limit ppm: 1500 WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: - | WEL 8-hr limit mg/m3: 1210 WEL 15 min limit mg/m3: 3620 WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: - |
| Butane | WEL 8-hr limit ppm: 600 WEL 15 min limit ppm: 750 WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: - | WEL 8-hr limit mg/m3: 1450 WEL 15 min limit mg/m3: 1810 WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: - |
| Isobutane | WEL 8-hr limit ppm: 800 WEL 15 min limit ppm: 800 WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: - | WEL 8-hr limit mg/m3: WEL 15 min limit mg/m3: WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: - |

DNEL: Derived no-effect level.

No data is available on this product.

8.2. Exposure controls

| | |
|---|--|
| 8.2.1. Appropriate engineering controls | Ensure adequate ventilation of the working area. |
| 8.2.2. Individual protection measures | Wear suitable protective equipment. |
| Eye / face protection | Approved safety goggles. |
| Skin protection - Handprotection | Chemical resistant gloves (PVC). |
| Respiratory protection | Not normally required. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--------------------------|---------------------|
| Appearance | Aerosol |
| Colour | Amber |
| Odour | Characteristic |
| Flash point | < -10 |
| Upper Explosive Limit | No data available |
| Lower Explosive Limit | No data available |
| Relative density | Not applicable. |
| Autoignition temperature | No data available |
| Explosive properties | No data available |
| Solubility | Immiscible in water |

9.2. Other information

VOC (Volatile organic compounds) > 70

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

K 1012 PENERATING OIL

Revision 0

Revision date 2016-03-23

10.3. Possibility of hazardous reactions

Oxidising agents.

10.4. Conditions to avoid

Heat, sparks and open flames.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|---------------------------|---|
| Skin corrosion/irritation | May cause degreasing of the skin. May cause severe irritation to eyes and skin. |
|---------------------------|---|

SECTION 12: Ecological information

12.2. Persistence and degradability

Evaporates readily.

12.3. Bioaccumulative potential

Does not bioaccumulate.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

| | |
|-----------------|----------|
| ADR/RID | 2 |
| Subsidiary risk | see SP63 |
| IMDG | 2 |
| Subsidiary risk | see SP63 |
| IATA | 2 |
| Subsidiary risk | see SP63 |

14.4. Packing group

Packing group

-

14.5. Environmental hazards

| | |
|-----------------------|----|
| Environmental hazards | No |
| Marine pollutant | No |

ADR/RID

| | |
|-----------------|-----|
| Hazard ID | - |
| Tunnel Category | (D) |

IMDG

K 1012 PENERATING OIL

Revision 0

Revision date 2016-03-23

| IMDG | |
|---------------------------------|---------|
| EmS Code | F-D S-U |
| IATA | |
| Packing Instruction (Cargo) | 203 |
| Maximum quantity | 150 kg |
| Packing Instruction (Passenger) | 203 |
| Maximum quantity | 75 kg |

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

| | |
|--------------------|---|
| | <p>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.</p> <p>Approved Code of Practice Safety Data Sheets for substances and Preparations, Classification and Labelling of Substances and Preparations Dangerous for supply. Guidance Notes</p> <p>Workplace Exposure Limits EH40 EU Legislation</p> <p>Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC), 793/93 and Commission Regulation (EC) No 1488/94 and as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) no 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (E/C) No 1907/2006 with amendments. National Regulations</p> <p>The Aerosol Dispensers Regulations 2009 SI 2824) The Aerosol Dispensers (EEC Requirements) (Amendment) Regulations 1996 (SI 1996 No 2421). Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous with waste with amendments. Health and Environmental Listings.</p> <p>Regulation EC 689/2008 concerning the export and import of dangerous chemicals. Water hazard classification</p> <p>WGK 1.</p> |
| Regulations | <p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> |

K 1012 PENERATING OIL

Revision 0

Revision date 2016-03-23

15.2. Chemical safety assessment

| | |
|--|---|
| | No chemical Safety assessment has been carried out by the supplier. |
|--|---|

SECTION 16: Other information

Other information

| | |
|---|---|
| Text of risk phrases in Section 3 | R11 - Highly flammable. R12 - Extremely flammable. R36/38 - Irritating to eyes and skin. R36 - Irritating to eyes. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness. |
| Text of Hazard Statements in Section 3 | Flam. Gas 1: H220 - Extremely flammable gas. Flam. Liq. 3: H226 - Flammable liquid and vapour. |
| Maximum content of VOC | 70. |

Further information

| | |
|--|--|
| | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. |
|--|--|